


CERTIGRADE® Shingles



Smooth sawn, architecturally uniform cedar shingles offer a natural and tailored appearance. Shingles are used on traditional and modern roof and wall applications (sidewall projects requiring additional machining on all four shingle edges should be specified as R&R sidewall shingles – see the sidewall section of this catalog.) Note that Number 1 Grade is the highest grade of shingle available – there is no such thing as a Premium Grade shingle.

Species / Grade / Description / Recommended Use Consult CSSB grading rules and installation manuals for detailed specifications.



WESTERN RED CEDAR Number 1 Grade (highest grade)

Clear heartwood, 100% edge grain, no defects.

Lengths: 16-inch (Fivex), 18-inch (Perfection), 24-inch (Royal).


Thicknesses: 16-inch is 5/2" (5 butts together measure 2" thick), 18-inch is 5/2¼", 24-inch is 4/2".

Recommended Use: For roofs of 4:12 slope and steeper and walls where a top quality product is desired.

Photo below shows Certi-label™ Western Red Cedar installation:



Photo: Mario Novak, Architect: Bob Ortmann, Zwirko & Ortmann Architects, PC, Builder: Telemark Inc.



YELLOW CEDAR Number 1 Grade (highest grade)

Clear heartwood, 100% edge grain, no defects.

Lengths: 18-inch (Perfection).

Thicknesses: 5/2¼" (5 butts together measure 2¼" thick).

Recommended Use: For roofs of 4:12 slope and steeper and walls where a top quality product is desired.

Yellow Cedar Certi-labels™ are distinguished by the brown color stripe underneath the top half of the label.